

TACWAY SLIDEWAY OIL

DESCRIPTION

Tacky, extreme pressure anti-wear machine tool slideway oil. Contains antiwear additives and tackifiers to protect the tool and minimise "run-off".

SUMMARY OF BENEFITS

- Anti Corrosive
- High level of protection with its EP properties
- Provides good antirust and storage protection
- Good surface coating characteristics

SPECIFICATIONS

Tacway Slideway Oil meets the following international performance specifications:

- Cincinatti Machine
- GM LS EP 2
- AGMA 9005-E02
- ISO 12925-1 CKC/CKD
- DIN 51517 (3)
- US Steel 224
- Available in ISO 68 & 220 grades

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TACWAY SLIDEWAY OIL

TYPICAL CHARACTERISTICS

TACWAY SLIDEWAY OIL	Test Method	Units	68	220
Density @ 15°C	ASTM D1298	kg/L	0.866	0.884
Kinematic Viscosity				
@ 40°C	ASTM D445	cSt	68	220
@ 100°C	ASTM D445	cSt	8.6	18.8
Viscosity Index	ASTM D2270	-	97	95
Pour Point	ASTM D97	°C	-12	-9
Flash Point (COC)	ASTM D92	°C	218	219

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

68: IBC - 30073B, 205lt - 30073, 20lt - 32073

220: IBC - 30074B, 205lt - 30074, 20lt - 32074