

TOP GAS 600 SAE 40

GAS ENGINE OIL

DESCRIPTION

TOP GAS 600 is a premium stationary engine oil developed for the most severe applications in a CO-GEN engine with and without ebullient cooling.

SUMMARY OF BENEFITS

- Exceptional Oxidation and Nitration resistance
- Low Zinc
- High level of protection
- Exceptional detergent/dispersant properties
- Extensive eld service
- Cleaner engines
- Longer oil and filter and service life
- Suitable where corrosive fuels are used
- Excellent valve train protection
- Reduced level of combustion chamber ash

SPECIFICATIONS

Top Gas 600 SAE 40 meets the following international performance specifications:

- SAE Viscosity 40
- WAUKESHA 7044/7042

Top Gas 600 SAE 40 is suitable for use in a wide range of engines including:

- Caterpillar 3500, 3600 & C280 (self certied)
- Jenbacher
- Waukesha
- API CF

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TOP GAS 600 SAE 40

GAS ENGINE OIL

TYPICAL CHARACTERISTICS

TOP GAS 600	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.8871
Kinematic Viscosity @ 40°C	ASTM D445	cSt	124
@ 100°C	ASTM D445	cSt	13.5
Viscosity Index	ASTM D2270	-	104
Pour Point	ASTM D97	°C	-9
Flash Point (COC)	ASTM D92	°C	224
Total Base Number	ASTM D2896	mgKOH/g	4.2
Sulphated Ash	ASTM D874	% mass	0.5%

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 30033, 20lt - 32033, 5lt - 30533