

Safety Data Sheet

1. IDENTIFICATION OF THE MATERIAL AND THE SUPPLIER

Product Name	Tyre Shine
Product Code	62097 (20L)
Product Use	Tyre appearance product
Issue Date	September 2023
Company Name	Gulf Western Oil
Company Address	92 – 96 Links Rd St Marys NSW 2760 Australia
Telephone number / Fax	(02) 9673 9600 (phone) / (02) 9673 9696 (fax)
Emergency Telephone number	(02) 9673 9600 (business hours) or 131 126 (Poisons Information Centre)
Other Information	Not applicable

2. HAZARDS IDENTIFICATION





GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS7) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Signal Word: DANGER

Safety Data Sheet

Flammable Liquids, Category 2		H225 Highly flammable liquid and vapour
Aspiration Hazard, Category 1 Toxic to Reproduction, Category 2 Specific Target Organ Toxicity (Repeated exposure), Category 2		H304 May be fatal if swallowed and enters airways H361 Suspected of damaging the unborn child H373 May cause damage to organs through prolonged or repeated
Skin Corrosion/Irritation, Category 2 Specific Target Organ Toxicity (Single exposure), Category 3		H315 Causes skin irritation H336 May cause drowsiness or dizziness
Chronic Aquatic Toxicity, Category 2		H411 Toxic to aquatic life with long lasting effects

Precautionary statements:

GENERAL

P101	If medical advice is needed, have product container or label at hand
P102	Keep out of reach of children
P103	Read label before use

Safety Data Sheet

PREVENTATIVE

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilation/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe mist/vapours/spray
P261	Avoid breathing mist/vapours/spray
P264	Wash thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P273	Avoid release to the environment
P280	Wear protective gloves/eye protection/face protection
P281	Use personal protective equipment as required

RESPONSE

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P303 + P361 + P353	IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Rinse skin with water/shower
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P308 + P313	IF exposed or concerned: Get medical advice/attention
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get medical advice/attention if you feel unwell
P331	Do NOT induce vomiting
P332 + P313	If skin irritation occurs: Get medical advice/attention
P362	Take off contaminated clothing and wash before reuse
P370 + P378	In case of fire: Use foam/water spray/fog for extinction
P391	Collect spillage

STORAGE

P403 + P233	Store in a well-ventilated place. Keep container tightly closed
-------------	---

Safety Data Sheet

P403 + P235	Store in a well-ventilated place. Keep cool
P405	Store locked up

3. COMPOSITION / INFORMATION ON INGREDIENTS

Composition information

INGREDIENT NAME	CAS NO.	WEIGHT
Solvent naphtha	64742-89-8	>60%
Polydimethyl siloxane	63148-62-9	10 – 30%

4. FIRST AID MEASURES

Inhaled

Vapour inhalation under ambient conditions is normally not a problem. If fumes or combustion products are inhaled the removed affected person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion

Aspiration hazard. If swallowed, do not induce vomiting. Immediately wash out mouth with water. Immediately seek medical attention. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Call a doctor immediately.

Skin

Remove contaminated clothing wipe off excess with absorbent tissue or towel and wash skin thoroughly with soap and water. Immediately flush skin with plenty of soap and water for at least 15 minutes. If swelling, redness, blisters or irritation develops and persists seek medical attention.

Eye


If contact occurs, immediately wash with running water for 15 minutes, holding eyelids open. Continue flushing until advised to stop by the Poisons Information Centre, or a doctor, or for at least 15 minutes. Removal of contact lenses after eye injury should only be undertaken by skilled personnel.

First Aid Facilities

Eye wash and normal washroom facilities.

Advice to Doctor

Treat symptomatically.



Safety Data Sheet

5. FIRE FIGHTING MEASURES

Flammable Liquid and Vapor! Contact with strong oxidizers may cause fire.

Flash point: <0°C Closed Cup

Autoignition temperature: not available

Flammable limits in air % by volume:

lower exposure limit: 1.1; upper exposure limit: 5.9

Extinguishing Media

Dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool.

Specific Hazards

Sealed containers may rupture when heated. Above the flash point, explosive vapor-air mixtures may be formed. Vapors can flow along surfaces to distant ignition source and flash back.

Hazardous Combustion Products

During combustion this product may emit toxic and or / irritating fumes including oxides of carbon and nitrogen.

Precautions

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face-piece operated in the pressure demand or other positive pressure mode.


6. ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Remove all sources of ignition. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

Personal Precautions

Wear appropriate personal protective equipment. Minimise skin contact. Slippery when spilt.

Precautions To Protect The Environment



Safety Data Sheet

Keep product out of sewers and watercourses by isolating or compounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.

Spill Clean up Procedures

Avoid contact with eyes or skin. Place leaking containers in well ventilated area. Avoid discharge to natural waterways. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

7. HANDLING AND STORAGE

Corrosiveness

Not corrosive.

Handling

Do not reuse container. Keep lid closed when not in use. Do not store or mix with strong oxidizers. Avoid spilling.

Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for

the product. Do not attempt to clean empty containers since residue is difficult to remove. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Worksafe exposure standard:-

Time Weighted Average (TWA)	300mg/m3	-
-----------------------------	----------	---

Safety Data Sheet

Short Term Exposure Limit (STEL) - -

Respiratory Protection

Avoid breathing vapours or mists. Where ventilation is inadequate and vapours or mists are generated the use of an approved respirator with organic vapour/particulate filter complying with AS/NZS 1715 and AS/NZS 1716 is recommended.

Eye Protection

Wear splash proof eye goggles to prevent any possibility of eye contact.

Hand Protection

Wear gloves of impervious material if handling material for prolonged periods.

Body Protection

Wear appropriate clothing including chemical resistant apron where clothing is likely to be contaminated.

Engineering controls

Natural ventilation should be sufficient, however where vapours or mists are generated (either through confinement or elevated temperatures) the use of a local exhaust system is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / Description	Clear colourless mobile liquid.
Boiling Point	70 – 135 °C
Solubility in Water	Insoluble
Specific Gravity	0.695 g/mL
Vapour Pressure	15 kPa @ 20°C
Viscosity	Not applicable
Flash Point	<0°C
Flammability	LEL – 1.1; UEL – 7.5 % by volume

Safety Data Sheet

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Hazardous Polymerization

Will not occur.

Materials to Avoid

Strong oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition and combustion produce noxious fumes containing oxides of carbon

Hazardous Reaction

Hazardous reaction with strong oxidizing agents

Conditions to Avoid

Heat, ignition sources. Avoid contact with acids and oxidizing substances.

11. TOXICOLOGICAL INFORMATION

Toxicological Information

POTENTIAL HEALTH EFFECTS

Ingestion

Harmful. Ingestion will irritate the gastric tract which may cause nausea and vomiting. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis.

Inhalation

Harmful. Inhalation of vapours or mists may cause irritation to the respiratory system. Inhalation of high concentrations may lead to headache, dizziness, nausea, vomiting or drowsiness.

Skin

Harmful. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Eye

Liquid and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

Chronic Effects

Prolonged or repeated skin contact may cause irritation leading to dermatitis. Prolonged inhalation of high vapour concentrations may cause drowsiness and lead to narcosis.

Safety Data Sheet

12. ECOLOGICAL INFORMATION

When released into the soil, this material may biodegrade to a moderate extent. When released into the soil, this material may evaporate to a moderate extent. When released into water, this material may biodegrade to a moderate extent. This material may bioaccumulate to some extent. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals.

Environmental Protection

Prevent this material from entering the environment

Ecotoxicity

No specific data is available for this product.

Persistence / Degradability

No specific data is available for this product.

Mobility

No specific data is available for this product.

Bioaccumulation

No specific data is available for this product.


13. DISPOSAL CONSIDERATIONS

Contain the spill with sand or earth or absorb with absorbent material. Collect the material and place into a suitably sealed and labeled container. Do not allow the product to enter drains, sewers or water courses. If large quantities of this material enters the waterways contact the Environmental Protection Authority, or your local Waste Management Authority. Recycle container if authorities permit it and facilities are available.

14. TRANSPORT INFORMATION

Classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

UN Number



Safety Data Sheet

1268

Proper Shipping Name

PETROLEUM DISTILLATES, N.O.S. (solvent naphtha, light aliphatic)

DG class

3 (Flammable Liquid)

Hazchem Code

3[Y]E

Packing Group

II

15. REGULATORY INFORMATION

Poisons Schedule

Schedule 5 Poison according to the Standard for Uniform Scheduling of Medicines and Poisons

Australian Inventory of Chemical Substances (AICS) and New Zealand Inventory of Chemicals (NZIoC)

All individual components are registered on the Australian and New Zealand Inventory of Chemical Substances

16. OTHER INFORMATION


Contact Person

For information concerning details on this Safety Data Sheet contact the Technical Manager on the following number:

(02) 9673 9600 (business hours)

General Disclaimer

All reasonable care has been taken to ensure that the information and advice contained herein are accurate at the time of printing. Gulf Western Oil however accepts no liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein.



Safety Data Sheet

History

This Safety Data Sheet prepared in November 2013

Complete Revision – August 2018

September 2023 – GHS7 confirmation, formulation checked, pictogram/hazard/response statements updated