

TECHNICAL DATA SHEET

TYRE SHINE



DESCRIPTION

Gulf Western Tyre Shine is a high quality silicone tyre treatment. It is a specially formulated blend of different types of silicone to enhance light reflectivity and broad coverage. Gulf Western Tyre Shine is formulated with silicones that provide a consistent, shiny finish when applied correctly that will rejuvenate tyres and aged vinyl. It resists water and outlasts most tyre shine products available. It is also economical and efficient to use. May be sprayed, painted or wiped onto surfaces. Best results are achieved by spraying surface evenly and allowing 15 minutes to dry. Should faster drying be necessary wiping with a clean rag after spraying may be necessary. This may leave a slightly less shiny finish. Note: The appearance of tyre shine after application to the tyre will vary depending upon the age and condition of the tyre. Newer tyres can repel the silicone due to the presence of coating from manufacturing and older tyres can soak up the silicone very readily thereby diminishing the gloss of the finish.

WARNING

Intentional misuse by deliberately concentrating or inhaling contents can be harmful or fatal. Keep in a cool dry place away from sun. Do not store above 50°C. Do not use near fire or naked flame. Do not incinerate this can even when empty. Dispose of waste residues and empty cans thoughtfully.

TYPICAL CHARACTERISTICS	
APPEARANCE:	Clear Liquid
ODOUR:	Solvent / Petroleum Odour
SOLUBILITY:	Not Soluble in Water
FLAMMABLE:	Highly Flammable
ADG CODE:	Class 3 Flammable (Packing Group II)
SPECIFIC GRAVITY:	0.72 - 0.75

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

20L - #62097

February 2022

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au