TECHNICAL DATA SHEET

MOULD RELEASE

GULF WESTERN OIL
GO THE DISTANCE

DESCRIPTION

MOULD RELEASE is a general purpose concrete mould release. Concrete work is normally formed. Hence, we refer to the oil as a release agent suitable for form materials, eg. Steel, wood, plywood, hardboard etc. A release agent is applied to formwork prior to placing concrete against the form. It provides a film at the framework/concrete interface interface which facilitates stripping and at the same time minimises blemishes to the concrete surface.

APPLICATION

MOULD RELEASE is an economical release agent for the manufacture of concrete slabs and pre-stressed concrete.

PHYSICAL PROPERTIES

MOULD RELEASE	RESULTS
APPEARANCE	GOLDEN
ODOUR	BLAND OILY
DENSITY @ 15%	0.8454
FLASH POINT	>70°C
KINEMATIC VISCOSITY @ 40°C mm2/s (cst)	5.2

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

IBC - #300419B, 205LT - #300419, 20LT - #320419

October 2026

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD
Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
Phone: 02 9673 9600 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au